

DEK Electroform Variable Aperture Height Technology (VAHT)

DEK VAHT technology offers a unique alternative to multi-level stencils for non-homogeneous assemblies that call for larger, area-specific paste volumes to accommodate bigger components.



Electroform stencils can be produced with modifications to accommodate specific applications. One such adaptation is a technique called Variable Aperture Height Technology (VAHT), whereby a gasket overgrowth is created around apertures to create more aperture height to allow for increased paste volumes to be deposited.

VAHT is ideal for PCBs that incorporate both small and large components that require varying amounts of solder material. Aperture gasket height can be 1 to 2 mils higher than the base stencil thickness.

Benefits:

- Ideal for heterogeneous assemblies, allowing printing of various solder paste volumes with a single stencil
- Improved throughput



ASMPT Americas

Phone: +888 768 4357 (press 2)

Email: smtparts.us@asmpt.com

ASMPT Europe

Phone: +40 722 692 108

Email: asmpt-psp.eu@asmpt.com

ASMPT Asia

Phone: +65 6877 3900

Email: spares.sg@asmpt.com





Process Support Products Website

psp.smt.asmpt.com



Process Support Products Webshop

> smt.asmpt.com/en/ myasmpt/webshop



ASMPT SMT Solutions Website

smt.asmpt.com



ASMPT Website

asmpt.com



ASMPT SMT Solutions YouTube

> www.youtube.com/c/ ASMPTSMTSolutions

Edition 9/01-2023 | All rights reserved. All rights reserved. | Order No.: A22-ASMPT-A322-EN | Printed in Germany | © ASMPT GmbH & Co. KG

All information and illustrations in this brochure are provided "as is" and without any warranties of any kind, whether expressed or implied, including but not limited to, implied warranties of satisfactory quality, fitness for a particular purpose and/or correctness.

The contents of this brochure are for general information purposes only, do not constitute advice, and are subject to change without notice. ASMPT therefore makes no warranties or representations regarding the use of the content, details, specifications or information contained in this brochure in terms of their correctness, accuracy, adequacy, usefulness, timeliness, reliability or otherwise, in each case to the fullest extent permitted by law. Please contact ASMPT for the most current information. Any specific performance features and/or capabilities will only be binding if contractually agreed upon.

All product names are brands or trademarks of ASMPT or other suppliers. Unauthorised use by third parties may violate the rights of their owners.